

# The **preview** Package for L<sup>A</sup>T<sub>E</sub>X

## Version 12.3

David Kastrup\*

2017/04/24

## 1 Introduction

The main purpose of this package is the extraction of certain environments (most notably displayed formulas) from L<sup>A</sup>T<sub>E</sub>X sources as graphics. This works with DVI files postprocessed by either Dvips and Ghostscript or dvipng, but it also works when you are using PDF<sup>T</sup><sub>E</sub>X for generating PDF files (usually also postprocessed by Ghostscript).

Current uses of the package include the **preview-latex** package for WYSIWYG functionality in the AUC<sup>T</sup><sub>E</sub>X editing environment, generation of previews in LyX, as part of the operation of the pst-pdf package, the tbook XML system and some other tools.

Producing EPS files with Dvips and its derivatives using the **-E** option is not a good alternative: People make do by fiddling around with `\thispagestyle{empty}` and hoping for the best (namely, that the specified contents will indeed fit on single pages), and then trying to guess the baseline of the resulting code and stuff, but this is at best dissatisfactory. The preview package provides an easy way to ensure that exactly one page per request gets shipped, with a well-defined baseline and no page decorations. While you still can use the preview package with the ‘classic’

`dvips -E -i`

invocation, there are better ways available that don’t rely on Dvips not getting confused by PostScript specials.

For most applications, you’ll want to make use of the **tightpage** option. This will embed the page dimensions into the PostScript or PDF code, obliterating the need to use the **-E -i** options to Dvips. You can then produce all image files with a single run of Ghostscript from a single PDF or PostScript (as opposed to EPS) file.

---

\*bug-auctex@gnu.org

Various options exist that will pass  $\TeX$  dimensions and other information about the respective shipped out material (including descender size) into the log file, where external applications might make use of it.

The possibility for generating a whole set of graphics with a single run of Ghostscript (whether from  $\LaTeX$  or  $\PDFLaTeX$ ) increases both speed and robustness of applications. It is also feasible to use `dvipng` on a DVI file with the options

```
-picky -noghostscript
```

to omit generating any image file that requires Ghostscript, then let a script generate all missing files using `Dvips`/`Ghostscript`. This will usually speed up the process significantly.

## 2 Package options

The package is included with the customary

```
\usepackage[<options>]{preview}
```

You should usually load this package as the last one, since it redefines several things that other packages may also provide.

The following options are available:

**active** is the most essential option. If this option is not specified, the **preview** package will be inactive and the document will be typeset as if the **preview** package were not loaded, except that all declarations and environments defined by the package are still legal but have no effect. This allows defining previewing characteristics in your document, and only activating them by calling  $\LaTeX$  as

```
latex '\PassOptionsToPackage{active}{preview}
\input{<filename>}'
```

**noconfig** Usually the file `prdefault.cfg` gets loaded whenever the **preview** package gets activated. `prdefault.cfg` is supposed to contain definitions that can cater for otherwise bad results, for example, if a certain document class would otherwise lead to trouble. It also can be used to override any settings made in this package, since it is loaded at the very end of it. In addition, there may be configuration files specific for certain **preview** options like **auctex** which have more immediate needs. The **noconfig** option suppresses loading of those option files, too.

**psfixbb** `Dvips` determines the bounding boxes from the material in the DVI file it understands. Lots of PostScript specials are not part of that. Since the  $\TeX$  boxes do not make it into the DVI file, but merely characters, rules and specials do, `Dvips` might include far too small areas. The option **psfixbb** will include `/dev/null` as a graphic file in the ultimate upper left and lower right corner of the previewed box. This will make `Dvips` generate an appropriate bounding box.

**dvips** If this option is specified as a class option or to other packages, several packages pass things like page size information to Dvips, or cause crop marks or draft messages written on pages. This seriously hampers the usability of previews. If this option is specified, the changes will be undone if possible.

**pdftex** If this option is set, PDF<sub>T</sub><sub>E</sub>X is assumed as the output driver. This mainly affects the **tightpage** option.

**xetex** If this option is set, Xe<sub>T</sub><sub>E</sub>X is assumed as the output driver. This mainly affects the **tightpage** option.

**displaymath** will make all displayed math environments subject to preview processing. This will typically be the most desired option.

**floats** will make all float objects subject to preview processing. If you want to be more selective about what floats to pass through to a preview, you should instead use the `\PreviewSnarfEnvironment` command on the floats you want to have previewed.

**textmath** will make all text math subject to previews. Since math mode is used thoroughly inside of L<sup>A</sup>T<sub>E</sub>X even for other purposes, this works by redefining `\(, \)` and `$` and the `math` environment (apparently some people use that). Only occurrences of these text math delimiters in later loaded packages and in the main document will thus be affected.

**graphics** will subject all `\includegraphics` commands to a preview.

**sections** will subject all section headers to a preview.

**delayed** will delay all activations and redefinitions the **preview** package makes until `\begin{document}`. The purpose of this is to cater for documents which should be subjected to the **preview** package without having been prepared for it. You can process such documents with

```
latex '\RequirePackage[active,delayed,<options>]{preview}
\input{<filename>}'
```

This relaxes the requirement to be loading the **preview** package as last package.

`<driver>` loads a special driver file `pr<driver>.def`. The remaining options are implemented through the use of driver files.

**auctex** This driver will produce fake error messages at the start and end of every preview environment that enable the Emacs package **preview-latex** in connection with AUC<sub>T</sub><sub>E</sub>X to pinpoint the exact source location where the previews have originated. Unfortunately, there is no other reliable means of passing the current T<sub>E</sub>X input position *in* a line to external programs. In order to make the parsing more robust, this option also switches off quite a few diagnostics that could be misinterpreted.

You should not specify this option manually, since it will only be needed by automated runs that want to parse the pseudo error messages. Those runs will then use `\PassOptionsToPackage` in order to effect the desired behaviour. In addition, `prauctex.cfg` will get loaded unless inhibited by the `noconfig` option. This caters for the most frequently encountered problematic commands.

**showlabels** During the editing process, some people like to see the label names in their equations, figures and the like. Now if you are using Emacs for editing, and in particular `preview-latex`, I'd strongly recommend that you check out the RefTeX package which pretty much obliterates the need for this kind of functionality. If you still want it, standard L<sup>A</sup>T<sub>E</sub>X provides it with the `showkeys` package, and there is also the less encompassing `showlabels` package. Unfortunately, since those go to some pain not to change the page layout and spacing, they also don't change `preview`'s idea of the T<sub>E</sub>X dimensions of the involved boxes. So if you are using `preview` for determining bounding boxes, those packages are mostly useless. The option `showlabels` offers a substitute for them.

**tightpage** It is not uncommon to want to use the results of `preview` as graphic images for some other application. One possibility is to generate a flurry of EPS files with

```
dvips -E -i -Pwww -o <outputfile>.000 <inputfile>
```

However, in case those are to be processed further into graphic image files by Ghostscript, this process is inefficient since all of those files need to be processed one by one. In addition, it is necessary to extract the bounding box comments from the EPS files and convert them into page dimension parameters for Ghostscript in order to avoid full-page graphics. This is not even possible if you wanted to use Ghostscript in a *single* run for generating the files from a single PostScript file, since Dvips will in that case leave no bounding box information anywhere.

The solution is to use the `tightpage` option. That way a single command line like

```
gs -sDEVICE=png16m -dTextAlphaBits=4 -r300
-dGraphicsAlphaBits=4 -dSAFER -q -dNOPAUSE
-sOutputFile=<outputfile>%d.png <inputfile>.ps
```

will be able to produce tight graphics from a single PostScript file generated with Dvips *without* use of the options `-E -i`, in a single run.

The `tightpage` option actually also works when using the `pdftex` option and generating PDF files with PDF<sub>T</sub>E<sub>X</sub>. The resulting PDF file has separate page dimensions for every page and can directly be converted with one run of Ghostscript into image files.

If neither `dvips` or `pdftex` have been specified, the corresponding option will get autodetected and invoked.

If you need this in a batch environment where you don't want to use `preview`'s automatic extraction facilities, no problem: just don't use any of the extraction options, and wrap everything to be previewed into `preview` environments. This is how LyX does its math previews.

If the pages under the `tightpage` option are just too tight, you can adjust by setting the length `\PreviewBorder` to a different value by using `\setlength`. The default value is `0.50001bp`, which is half of a usual PostScript point, rounded up. If you go below this value, the resulting page size may drop below `1bp`, and Ghostscript does not seem to like that. If you need finer control, you can adjust the bounding box dimensions individually by changing the macro `\PreviewBbAdjust` with the help of `\renewcommand`. Its default value is

```
\newcommand \PreviewBbAdjust {-\PreviewBorder
-\PreviewBorder \PreviewBorder \PreviewBorder}
```

This adjusts the left, lower, right and upper borders by the given amount. The macro must contain 4  $\TeX$  dimensions after another, and you may not omit the units if you specify them explicitly instead of by register. PostScript points have the unit `bp`.

**lyx** This option is for the sake of LyX developers. It will output a few diagnostics relevant for the sake of LyX' preview functionality (at the time of writing, mostly implemented for math insets, in versions of LyX starting with 1.3.0).

**counters** This writes out diagnostics at the start and the end of previews. Only the counters changed since the last output get written, and if no counters changed, nothing gets written at all. The list consists of counter name and value, both enclosed in `{}` braces, followed by a space. The last such pair is followed by a colon `(:)` if it is at the start of the preview snippet, and by a period `(.)` if it is at the end. The order of different diagnostics like this being issued depends on the order of the specification of the options when calling the package.

Systems like `preview-latex` use this for keeping counters accurate when single previews are regenerated.

**footnotes** This makes footnotes render as previews, and only as their footnote symbol. A convenient editing feature inside of Emacs.

The following options are just for debugging purposes of the package and similar to the corresponding  $\TeX$  commands they allude to:

**tracingall** causes lots of diagnostic output to appear in the log file during the preview collecting phases of  $\TeX$ 's operation. In contrast to the similarly named  $\TeX$  command, it will not switch to `\errorstopmode`, nor will it change the setting of `\tracingonline`.

**showbox** This option will show the contents of the boxes shipped out to the DVI files. It also sets `\showboxbreadth` and `\showboxdepth` to their maximum values at the end of loading this package, but you may reset them if you don't like that.

### 3 Provided Commands

**preview** The **preview** environment causes its contents to be set as a single preview image. Insertions like figures and footnotes (except those included in minipages) will typically lead to error messages or be lost. In case the **preview** package has not been activated, the contents of this environment will be typeset normally.

**nopreview** The **nopreview** environment will cause its contents not to undergo any special treatment by the **preview** package. When **preview** is active, the contents will be discarded like all main text that does not trigger the **preview** hooks. When **preview** is not active, the contents will be typeset just like the main text.

Note that both of these environments typeset things as usual when preview is not active. If you need something typeset conditionally, use the `\ifPreview` conditional for it.

**\PreviewMacro** If you want to make a macro like `\includegraphics` (actually, this is what is done by the **graphics** option to **preview**) produce a preview image, you put a declaration like

```
\PreviewMacro[*[!]{\includegraphics}
```

or, more readable,

```
\PreviewMacro[{*[] []}{\includegraphics}
```

into your preamble. The optional argument to `\PreviewMacro` specifies the arguments `\includegraphics` accepts, since this is necessary information for properly ending the preview box. Note that if you are using the more readable form, you have to enclose the argument in a `{` and `}` pair. The inner braces are necessary to stop any included `[]` pairs from prematurely ending the optional argument, and to make a single `{}` denoting an optional argument not get stripped away by TeX's argument parsing.

The letters simply mean

`*` indicates an optional `*` modifier, as in `\includegraphics*`.

`[` indicates an optional argument in brackets. This syntax is somewhat baroque, but brief.

`[]` also indicates an optional argument in brackets. Be sure to have enclosed the entire optional argument specification in an additional pair of braces as described above.

`!` indicates a mandatory argument.

{ } indicates the same. Again, be sure to have that additional level of braces around the whole argument specification.

? $\langle\textit{delimiter}\rangle\{\langle\textit{true case}\rangle\}\{\langle\textit{false case}\rangle\}$  is a conditional. The next character is checked against being equal to  $\langle\textit{delimiter}\rangle$ . If it is, the specification  $\langle\textit{true case}\rangle$  is used for the further parsing, otherwise  $\langle\textit{false case}\rangle$  will be employed. In neither case is something consumed from the input, so  $\{\langle\textit{true case}\rangle\}$  will still have to deal with the upcoming delimiter.

@ $\{\langle\textit{literal sequence}\rangle\}$  will insert the given sequence literally into the executed call of the command.

- will just drop the next token. It will probably be most often used in the true branch of a ? specification.

# $\{\langle\textit{argument}\rangle\}\{\langle\textit{replacement}\rangle\}$  is a transformation rule that calls a macro with the given argument and replacement text on the rest of the argument list. The replacement is used in the executed call of the command. This can be used for parsing arbitrary constructs. For example, the [] option could manually be implemented with the option string ? $\{\{\#\}\{\#\}\}\{\{\#\}\}\}\{\}$ . PSTricks users might enjoy this sort of flexibility.

: $\{\langle\textit{argument}\rangle\}\{\langle\textit{replacement}\rangle\}$  is again a transformation rule. As opposed to #, however, the result of the transformation is parsed again. You'll rarely need this.

There is a second optional argument in brackets that can be used to declare any default action to be taken instead. This is mostly for the sake of macros that influence numbering: you would want to keep their effects in that respect. The default action should use #1 for referring to the original (not the patched) command with the parsed options appended. Not specifying a second optional argument here is equivalent to specifying [#1].

`\PreviewMacro*` A similar invocation `\PreviewMacro*` simply throws the macro and all of its arguments declared in the manner above away. This is mostly useful for having things like `\footnote` not do their magic on their arguments. More often than not, you don't want to declare any arguments to scan to `\PreviewMacro*` since you would want the remaining arguments to be treated as usual text and typeset in that manner instead of being thrown away. An exception might be, say, sort keys for `\cite`.

A second optional argument in brackets can be used to declare any default action to be taken instead. This is for the sake of macros that influence numbering: you would want to keep their effects in that respect. The default action might use #1 for referring to the original (not the patched) command with the parsed options appended. Not specifying a second optional argument here is equivalent to specifying [] since the command usually gets thrown away.

As an example for using this argument, you might want to specify

```
\PreviewMacro*[{[]}] [#1{}]{\footnote}
```

This will replace a footnote by an empty footnote, but taking any optional parameter into account, since an optional parameter changes the numbering scheme. That way the real argument for the footnote remains for processing by `preview-latex`.

`\PreviewEnvironment`      The macro `\PreviewEnvironment` works just as `\PreviewMacro` does, only  
`\PreviewEnvironment*`      for environments. And the same goes for `\PreviewEnvironment*` as compared to  
`\PreviewMacro*`.

`\PreviewSnarfEnvironment`      This macro does not typeset the original environment inside of a preview box, but instead typesets just the contents of the original environment inside of the preview box, leaving nothing for the original environment. This has to be used for figures, for example, since they would

1. produce insertion material that cannot be extracted to the preview properly,
2. complain with an error message about not being in outer par mode.

`\PreviewOpen`      Those Macros form a matched preview pair. This is for macros that behave  
`\PreviewClose`      similar as `\begin` and `\end` of an environment. It is essential for the operation of `\PreviewOpen` that the macro treated with it will open an additional group even when the preview falls inside of another preview or inside of a `nopreview` environment. Similarly, the macro treated with `\PreviewClose` will close an environment even when inactive.

`\ifPreview`      In case you need to know whether `preview` is active, you can use the conditional `\ifPreview` together with `\else` and `\fi`.

## 4 The Implementation

Here we go: the start is somewhat obtuse since we figure out version number and date from RCS strings. This should really be done at docstrip time instead. Takers?

```
\pr@version
1 <*style>
2 <!*active>
3 \NeedsTeXFormat{LaTeX2e} \def\reserved@a #1#2$#3:
4 #4${\xdef#1{\reserved@c #2#4 $}} \def\reserved@c #1 #2$#{#1}
5 \begingroup \catcode'\_ =12
6 \reserved@a\pr@version $Name: release_12_3 $ \ifx\pr@version\@empty
7 \reserved@a\pr@version CVS-$Revision: 1.126 $ \endgroup \else
8 \def\next release_{} \lccode'\_ ='.
9 \edef\next{\lowercase{\endgroup
10 \def\noexpand\pr@version{\expandafter\next\pr@version}} \next \fi
11 \reserved@a\next $Date: 2017/04/24 13:20:00 $
12 \edef\next{\noexpand\ProvidesPackage{preview}%
13 [\next\space \pr@version\space (AUCTeX/preview-latex)]}
14 \next
```

Since many parts here will not be needed as long as the package is inactive, we will include them enclosed with `<*active>` and `</active>` guards. That way, we can append all of this stuff at a place where it does not get loaded if not necessary.



`\ifPreview` Setting the `\ifPreview` command should not be done by the user, so we don't use `\newif` here. As a consequence, there are no `\Previewtrue` and `\Previewfalse` commands.

```

15 \let\ifPreview\iffalse
16 \</!active>

```

`\ifpr@outer` We don't allow previews inside of previews. The macro `\ifpr@outer` can be used for checking whether we are outside of any preview code.

```

17 <*active>
18 \newif\ifpr@outer
19 \pr@outertrue
20 </active>

```

`\preview@delay` The usual meaning of `\preview@delay` is to just echo its argument in normal `preview` operation. If `preview` is inactive, it swallows its argument. If the `delayed` option is active, the contents will be passed to the `\AtBeginDocument` hook.

`\pr@advise` The core macro for modifying commands is `\pr@advise`. You pass it the original command name as first argument and what should be executed before the saved original command as second argument.

`\pr@advise@ship` The most often used macro for modifying commands is `\pr@advise@ship`. It receives three arguments. The first is the macro to modify, the second specifies some actions to be done inside of a box to be created before the original macro gets executed, the third one specifies actions after the original macro got executed.

`\pr@loadcfg` The macro `\pr@loadcfg` is used for loading in configuration files, unless disabled by the `noconfig` option. After discussion with maintainer of `pst-pdf` package Rolf Niepraschk (Thanks!), we add here a check for existence of `luatex85.sty` and load it if available. With this, `preview` will also work with newer `luatex` versions.

```

21 <!*active>
22 \let\preview@delay=\@gobble
23 \let\pr@advise=\@gobbletwo
24 \long\def\pr@advise@ship#1#2#3{
25 \def\pr@loadcfg#1{\InputIfFileExists{#1.cfg}{}}{}}
26 \IfFileExists{luatex85.sty}{\RequirePackage{luatex85}}{}}
27 \DeclareOption{noconfig}{\let\pr@loadcfg=\@gobble}

```

`\pr@addto@front` This adds code globally to the front of a macro.

```

28 \long\def\pr@addto@front#1#2{%
29 \toks@{#2}\toks@\expandafter{\the\expandafter\toks@#1}%
30 \xdef#1{\the\toks@}}

```

These commands get more interesting when `preview` is active:

```

31 \DeclareOption{active}{%
32 \let\ifPreview\iftrue
33 \def\pr@advise#1{%
34 \expandafter\pr@adviseii\cname pr@\string#1\endcname#1}%
35 \long\def\pr@advise@ship#1#2#3{\pr@advise#1{\pr@protect@ship{#2}{#3}}}%
36 \let\preview@delay\@firstofone}

```

`\pr@adviseii` Now `\pr@advise` needs its helper macro. In order to avoid recursive definitions, we advise only macros that are not yet advised. Or, more exactly, we throw away the old advice and only take the new one. We use eTeX's `\protected` where available for some extra robustness.

```

37 \long\def\pr@adviseii#1#2#3{\preview@delay{%
38   \ifx#1\relax \let#1#2\fi
39   \toks@{#3#1}%
40   \ifx\undefined\protected \else \protected\fi
41   \long\edef#2{\the\toks@}}}
```

The `delayed` option is easy to implement: this is *not* done with `\let` since at the course of document processing, L<sup>A</sup>T<sub>E</sub>X redefines `\AtBeginDocument` and we want to follow that redefinition.

```

42 \DeclareOption{delayed}{%
43   \ifPreview \def\preview@delay{\AtBeginDocument}\fi
44 }
```

`\ifpr@fixbb` Another conditional. `\ifpr@fixbb` tells us whether we want to surround the typeset materials with invisible rules so that Dvips gets the bounding boxes right for, say, pure PostScript inclusions.

If you are installing this on an operating system different from the one `preview` has been developed on, you might want to redefine `\pr@markerbox` in your `prdefault.cfg` file to use a file known to be empty, like `/dev/null` is under Unix. Make this redefinition depend on `\ifpr@fixbb` since only then `\pr@markerbox` will be defined.

```

45 \newif\ifpr@fixbb
46 \pr@fixbbfalse
47 \DeclareOption{psfixbb}{\ifPreview%
48   \pr@fixbbtrue
49   \newbox\pr@markerbox
50   \setbox\pr@markerbox\hbox{\special{psfile=/dev/null}}\fi
51 }
```

`\pr@graphicstype` The `dvips` option redefines the `bop-hook` to reset the page size.

```

52 \let\pr@graphicstype=\z@
53 \DeclareOption{dvips}{%
54   \let\pr@graphicstype\@ne
55   \preview@delay{\AtBeginDvi{%
56     \special{!/preview@version(\pr@version)def}
57     \special{!userdict begin/preview-bop-level 0 def}
58     /bop-hook{/preview-bop-level dup load dup 0 le{/isls false def}
59       /vsize 792 def/hsize 612 def}if 1 add store}bind def}
60     /eop-hook{/preview-bop-level dup load dup 0 gt{1 sub}if
61       store}bind def end}}}
```

The `pdftex` option just sets `\pr@graphicstype`.

```

62 \DeclareOption{pdftex}{%
63   \let\pr@graphicstype\tw@}
```

And so does the `xetex` option.

```
64 \DeclareOption{xetex}{%
65   \let\pr@graphicstype\thr@@}
66 \!/active)
```

## 4.1 The internals

Those are only needed if `preview` is active.

```
67 \*active)
```

`\pr@snippet` `\pr@snippet` is the current snippet number. We need a separate counter to `\c@page` since several other commands might fiddle with the page number.

```
68 \newcount\pr@snippet
69 \global\pr@snippet=1
```

`\pr@protect` This macro gets one argument which is unpacked and executed in typesetting situations where we are not yet inside of a preview.

```
70 \def\pr@protect{\ifx\protect\@typeset@protect
71   \ifpr@outer \expandafter\expandafter\expandafter
72     \@secondoftwo\fi\fi\@gobble}
```

`\pr@protect@ship` Now for the above mentioned `\pr@protect@ship`. This gets three arguments. The first is what to do at the beginning of the preview, the second what to do at the end, the third is the macro where we stored the original definition.

In case we are not in a typesetting situation, `\pr@protect@ship` leaves the stored macro to fend for its own. No better or worse protection than the original. And we only do anything different when `\ifpr@outer` turns out to be true.

```
73 \def\pr@protect@ship{\pr@protect{\@firstoftwo\pr@startbox}%
74   \@gobbletwo}
```

`\pr@insert` We don't want insertions to end up on our lists. So we disable them right now by replacing them with the following:

```
\pr@mark
\pr@marks
75 \def\pr@insert{\begingroup\afterassignment\pr@insertii\count@}
76 \def\pr@insertii{\endgroup\setbox\pr@box\ vbox}
```

Similar things hold for marks.

```
77 \def\pr@mark{\afterassignment}\toks@}
78 \def\pr@marks{\aftergroup\pr@mark\afterassignment}\count@}
```

`\pr@box` `\pr@startbox` Previews will be stored in `\box\pr@box`. `\pr@startbox` gets two arguments: code to execute immediately before the following stuff, code to execute afterwards. You have to cater for `\pr@endbox` being called at the right time yourself. We will use a `\vsplit` on the box later in order to remove any leading glues, penalties and similar stuff. For this reason we start off the box with an optimal break point.

```
79 \newbox\pr@box
80 \long\def\pr@startbox#1#2{%
81   \ifpr@outer
82     \toks@{#2}%
```

```

83 \edef\pr@cleanup{\the\toks@}%
84 \setbox\pr@box\vbox\bgroup
85 \break
86 \pr@outerfalse\@arrayparboxrestore
87 \let\insert\pr@insert
88 \let\mark\pr@mark
89 \let\marks\pr@marks
90 \expandafter\expandafter\expandafter
91 \pr@ship@start
92 \expandafter\@firstofone
93 \else
94 \expandafter \gobble
95 \fi{#1}}

```

`\pr@endbox` Cleaning up also is straightforward. If we have to watch the bounding  $\text{\TeX}$  box, we want to remove spurious skips. We also want to unwrap a possible single line paragraph, so that the box is not full line length. We use `\vsplit` to clean up leading glue and stuff, and we make some attempt of removing trailing ones. After that, we wrap up the box including possible material from `\AtBeginDvi`. If the `psfixbb` option is active, we adorn the upper left and lower right corners with copies of `\pr@markerbox`. The first few lines cater for  $\text{\LaTeX}$  hiding things like the code for `\paragraph` in `\everypar`.

```

96 \def\pr@endbox{%
97 \let\reserved@a\relax
98 \ifvmode \edef\reserved@a{\the\everypar}%
99 \ifx\reserved@a\@empty\else
100 \dimen@ \prevdepth
101 \noindent\par
102 \setbox\z@\lastbox\unskip\unpenalty
103 \prevdepth\dimen@
104 \setbox\z@\hbox\bgroup\penalty-\maxdimen\unhbox\z@
105 \ifnum\lastpenalty=-\maxdimen\egroup
106 \else\egroup\box\z@ \fi\fi\fi
107 \ifhmode \par\unskip\setbox\z@\lastbox
108 \nointerlineskip\hbox{\unhbox\z@/\}%
109 \else \unskip\unpenalty\unskip \fi
110 \egroup
111 \setbox\pr@box\vbox{%
112 \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
113 \@begindvi
114 \nointerlineskip
115 \splittopskip\z@skip\setbox\z@\vsplit\pr@box to\z@
116 \unvbox\z@
117 \nointerlineskip
118 %\color@setgroup
119 \box\pr@box
120 %\color@endgroup
121 }%

```

`\pr@ship@end` At this point, `\pr@ship@end` gets called. You must not under any circumstances change `\box\pr@box` in any way that would add typeset material at the front of it, except for PostScript header specials, since the front of `\box\pr@box` may contain stuff from `\AtBeginDvi`. `\pr@ship@end` contains two types of code additions: stuff that adds to `\box\pr@box`, like the `labels` option does, and stuff that measures out things or otherwise takes a look at the finished `\box\pr@box`, like the `auctex` or `showbox` option do. The former should use `\r@addto@front` for adding to this hook, the latter use `\@addto@macro` for adding at the end of this hook.

Note that we shift the output box up by its height via `\voffset`. This has three reasons: first we make sure that no package-inflicted non-zero value of `\voffset` or `\hoffset` will have any influence on the positioning of our box. Second we shift the box such that its basepoint will exactly be at the (1in,1in) mark defined by `TeX`. That way we can properly take ascenders into account. And the third reason is that `TeX` treats a `\hbox` and a `\vbox` differently with regard to the treating of its depth. Shifting `\voffset` and `\hoffset` can be inhibited by setting `\pr@offset@override`.

```

122 \pr@ship@end
123 {\let\protect\noexpand
124 \ifx\pr@offset@override\@undefined
125 \voffset=-\ht\pr@box
126 \hoffset=\z@
127 \fi
128 \c@page=\pr@snippet
129 \pr@shipout
130 \ifpr@fixbb\hbox{%
131 \dimen@=\wd\pr@box
132 \@tempdima=\ht\pr@box
133 \@tempdimb=\dp\pr@box
134 \box\pr@box
135 \llap{\raise\@tempdima\copy\pr@markerbox\kern\dimen@}%
136 \lower\@tempdimb\copy\pr@markerbox}%
137 \else \box\pr@box \fi}%
138 \global\advance\pr@snippet\@ne
139 \pr@cleanup
140 }
```

Oh, and we kill off the usual meaning of `\shipout` in case somebody makes a special output routine. The following test is pretty much the same as in `everyshi.sty`. One of its implications is that if someone does a `\shipout` of a `void` box, things will go horribly wrong.

`\shipout`

```

141 \let\pr@shipout=\shipout
142 \def\shipout{\deadcycles\z@\bgroup\setbox\z@\box\voidb@x
143 \afterassignment\pr@shipoutegroup\setbox\z@}
144 \def\pr@shipoutegroup{\ifvoid\z@ \expandafter\aftergroup\fi \egroup}
```

## 4.2 Parsing commands

`\pr@parseit` The following stuff is for parsing the arguments of commands we want to somehow  
`\pr@endparse` surround with stuff. Usage is  
`\pr@callafter`

```
\pr@callafter<aftertoken><parsestring>\pr@endparse
<macro><parameters>
```

`<aftertoken>` is stored away and gets executed once parsing completes, with its first argument being the parsed material. `<parsestring>` would be, for example for the `\includegraphics` macro, `*[!]`, an optional `*` argument followed by two optional arguments enclosed in `[]`, followed by one mandatory argument.

For the sake of a somewhat more intuitive syntax, we now support also the syntax `{*[]!}` in the optional argument. Since `TEX` strips redundant braces, we have to write `[{}]` in this syntax for a single mandatory argument. Hard to avoid. We use an unusual character for ending the parsing. The implementation is rather trivial.

```
145 \def\pr@parseit#1{\csname pr@parse#1\endcsname}
146 \let\pr@endparse=@percentchar
147 \def\next#1{%
148 \def\pr@callafter{%
149 \afterassignment\pr@parseit
150 \let#1= } }
151 \expandafter\next\csname pr@parse\pr@endparse\endcsname
```

`\pr@parse*` Straightforward, same mechanism L<sup>A</sup>T<sub>E</sub>X itself employs. We take some care not to pass potential `#` tokens unprotected through macros.

```
152 \long\expandafter\def\csname pr@parse*\endcsname#1\pr@endparse#2{%
153 \begingroup\toks@{#1\pr@endparse{#2}}%
154 \edef\next##1{\endgroup##1\the\toks@}%
155 \@ifstar{\next{\pr@parse*}}{\next\pr@parseit}}
```

`\pr@parse[` Copies optional parameters in brackets if present. The additional level of braces  
`\pr@brace` is necessary to ensure that braces the user might have put to hide a `]` bracket in an optional argument don't get lost. There will be no harm if such braces were not there at the start.

```
156 \long\expandafter\def\csname pr@parse[\endcsname#1\pr@endparse#2{%
157 \begingroup\toks@{#1\pr@endparse{#2}}%
158 \edef\next##1{\endgroup##1\the\toks@}%
159 \@ifnextchar[{\next\pr@bracket}{\next\pr@parseit}}
160 \long\def\pr@bracket#1\pr@endparse#2[#3]{%
161 \pr@parseit#1\pr@endparse{#2[#3]}}
```

`\pr@parse]` This is basically a do-nothing, so that we may use the syntax `{*[]!}` in the optional argument instead of the more concise but ugly `*[!]` which confuses the brace matchers of editors.

```
162 \expandafter\let\csname pr@parse]\endcsname=\pr@parseit
```

`\pr@parse` Mandatory arguments are perhaps easiest to parse.

```

\pr@parse! 163 \long\def\pr@parse#1\pr@endparse#2#3{%
164   \pr@parseit#1\pr@endparse{#2{#3}}}%
165 \expandafter\let\csname pr@parse!\endcsname=\pr@parse

```

`\pr@parse?` This does an explicit call of `\@ifnextchar` and forks into the given two alternatives

`\pr@parsecond` as a result.

```

166 \long\expandafter\def\csname pr@parse?\endcsname#1#2\pr@endparse#3{%
167   \begingroup\toks@{#2\pr@endparse{#3}}}%
168   \@ifnextchar#1{\pr@parsecond\@firstoftwo}%
169               {\pr@parsecond\@secondoftwo}}
170 \def\pr@parsecond#1{\expandafter\endgroup
171   \expandafter\expandafter\expandafter\pr@parseit
172   \expandafter#1\the\toks@}

```

`\pr@parse@` This makes it possible to insert literal material into the argument list.

```

173 \long\def\pr@parse@#1#2\pr@endparse#3{%
174   \pr@parseit #2\pr@endparse{#3#1}}

```

`\pr@parse-` This will just drop the next token.

```

175 \long\expandafter\def\csname pr@parse-\endcsname
176   #1\pr@endparse#2{\begingroup
177     \toks@{\endgroup\pr@parseit #1\pr@endparse{#2}}}%
178   {\aftergroup\the\aftergroup\toks@ \afterassignment}%
179   \let\next= }

```

`\pr@parse:` The following is a transform rule. A macro is being defined with the given argument list and replacement, and the transformed version replaces the original. The result of the transform is still subject to being parsed.

```

180 \long\expandafter\def\csname pr@parse:\endcsname
181   #1#2#3\pr@endparse#4{\begingroup
182     \toks@{\endgroup \pr@parseit#3\pr@endparse{#4}}}%
183   \long\def\next#1{#2}%
184   \the\expandafter\toks@\next}

```

`\pr@parse#` Another transform rule, but this passes the transformed material into the token list.

```

185 \long\expandafter\def\csname pr@parse#\endcsname
186   #1#2#3\pr@endparse#4{\begingroup
187     \toks@{#4}}%
188     \long\edef\next##1{\toks@{\the\toks@##1}}%
189     \toks@{\endgroup \pr@parseit#3\pr@endparse}%
190     \long\def\reserved@a#1{#2}%
191     \the\expandafter\next\reserved@a}
192 </active>

```

### 4.3 Selection options

The `displaymath` option. The `equation` environments in AMS $\text{\LaTeX}$  already do too much before our hook gets to interfere, so we hook earlier. Some juggling is involved to ensure we get the original `\everydisplay` tokens only once and where appropriate.

The incredible hack with `\dt@ptrue` is necessary for working around bug ‘amslatex/3425’.

```

193 <!*active>
194 \begingroup
195 \catcode'\*=11
196 \@firstofone{\endgroup
197 \DeclareOption{displaymath}{%
198   \preview@delay{\toks@{%
199     \pr@startbox{\noindent$$%
200       \aftergroup\pr@endbox\@gobbletwo}{$$$}\@firstofone}%
201     \everydisplay\expandafter{\the\expandafter\toks@
202       \expandafter{\the\everydisplay}}}%
203   \pr@advise@ship\equation{\begingroup\aftergroup\pr@endbox
204     \def\dt@ptrue{\m@ne=\m@ne}\noindent}%
205     {\endgroup}%
206   \pr@advise@ship\equation*{\begingroup\aftergroup\pr@endbox
207     \def\dt@ptrue{\m@ne=\m@ne}\noindent}%
208     {\endgroup}%
209   \PreviewOpen[][\def\dt@ptrue{\m@ne=\m@ne}\noindent#1]\[%
210   \PreviewClose}%
211   \PreviewEnvironment[][\noindent#1]{eqnarray}%
212   \PreviewEnvironment[][\noindent#1]{eqnarray*}%
213   \PreviewEnvironment{displaymath}%
214 }}

```

The `textmath` option. Some folderol in order to define the active `$` math mode delimiter. `\pr@textmathcheck` is used for checking whether we have a single `$` or double `$$`. In the latter case, we enter display math (this sort of display math is not allowed inside of  $\text{\LaTeX}$  because of inconsistent spacing, but surprisingly many people use it nevertheless). Strictly speaking, this is incorrect, since not every `$$` actually means display math. For example, `\hbox{$$$}` will because of restricted horizontal mode rather yield an empty text math formula. Since our implementation moved the sequence inside of a `\vbox`, the interpretation will change. People should just not enter rubbish like that.

```

215 \begingroup
216 \def\next#1#2{%
217   \endgroup
218   \DeclareOption{textmath}{%
219     \PreviewEnvironment{math}%
220     \preview@delay{\ifx#1\undefined \let#1=$%$
221       \fi\catcode'\$=\active
222       \ifx\xyreuncatcodes\undefined\else
223         \edef\next{\catcode'\@=\the\catcode'\@relax}%

```



```

224 \makeatother\expandafter\xyreuncatcodes\next\fi}%
225 \pr@advise@ship\(\pr@endaftergroup{}}% \)
226 \pr@advise@ship#1{\@firstoftwo{\let#1=#2%
227 \futurelet\reserved@a\pr@textmathcheck}}{}}%
228 \def\pr@textmathcheck{\expandafter\pr@endaftergroup
229 \ifx\reserved@a#1{#2#2}\expandafter\@gobbletwo\fi#2}}
230 \lccode'\~='\'$
231 \lowercase{\expandafter\next\expandafter~}%
232 \csname pr@\string$}%$
233 \endcsname
234 \!/active)

```

\pr@endaftergroup This just ends the box after the group opened by #1 is closed again.

```

235 <*active>
236 \def\pr@endaftergroup#1{#1\aftergroup\pr@endbox}
237 </active>

```

The graphics option.

```

238 <!*active>
239 \DeclareOption{graphics}{%
240 \PreviewMacro[*[!]{\includegraphics}{}]}
241 }

```

The floats option. The complications here are merely to spare us bug reports about broken document classes that use \let on \endfigure and similar. Notable culprits that have not been changed in years in spite of reports are elsart.cls and IEEEtran.cls. Complain when you are concerned.

```

242 \def\pr@floatfix#1#2{\ifx#1#2%
243 \ifx#1\@undefined\else
244 \PackageWarningNoLine{preview}{%
245 Your document class has a bad definition^^J
246 of \string#1, most likely^^J
247 \string\let\string#1=\string#2^^J
248 which has now been changed to^^J
249 \string\def\string#1{\string#2}^^J
250 because otherwise subsequent changes to \string#2^^J
251 (like done by several packages changing float behaviour)^^J
252 can't take effect on \string#1.^^J
253 Please complain to your document class author}%
254 \def#1{#2}\fi\fi}
255 \begingroup
256 \def\next#1#2{\endgroup
257 \DeclareOption{floats}{%
258 \pr@floatfix\endfigure\end@float
259 \pr@floatfix\endtable\end@float
260 \pr@floatfix#1\end@dblfloat
261 \pr@floatfix#2\end@dblfloat
262 \PreviewSnarfEnvironment[![]{@float}]}
263 \PreviewSnarfEnvironment[![]{@dblfloat}]}
264 }}

```

```

265 \expandafter\next\csname endfigure*\expandafter\endcsname
266 \csname endtable*\endcsname

```

The `sections` option. Two optional parameters might occur in `memoir.cls`.

```

267 \DeclareOption{sections}{%
268   \PreviewMacro[!!!!*[[!]]{\@startsection}%]]
269   \PreviewMacro[*[[!]]{\chapter}%]]
270 }

```

We now interpret any further options as driver files we load. Note that these driver files are loaded even when `preview` is not active. The reason is that they might define commands (like `\PreviewCommand`) that should be available even in case of an inactive package. Large parts of the `preview` package will not have been loaded in this case: you have to cater for that.

```

271 \DeclareOption*
272   {\InputIfFileExists{pr\CurrentOption.def}{\OptionNotUsed}}

```

## 4.4 Preview attaching commands

`\PreviewMacro` As explained above. Detect possible `*` and call appropriate macro.

```

273 \def\PreviewMacro{\@ifstar\pr@starmacro\pr@macro}

```

The version without `*` is now rather straightforward.

```

\pr@macro
\pr@domacro 274 \long\def\pr@domacro#1#2{%
\pr@macroii 275   \long\def\next##1{#2}%
\pr@endmacro 276   \pr@callafter\next#1\pr@endparse}
277 \newcommand\pr@macro[1][\]{%
278   \toks@{\pr@domacro{#1}}%
279   \long\edef\next[##1]##2{%
280     \noexpand\pr@advise@ship{##2}{\the\toks@{##1\noexpand\pr@endbox}}}%
281   \@ifnextchar[\next\pr@macroii}
282 \def\pr@macroii{\next[##1]}
283 \long\def\pr@endmacro#1{#1\pr@endbox}

```

`PreviewMacro*` The version with `*` has to parse the arguments, then throw them away. Some internal macros first, then the interface call.

```

\pr@protect@domacro
\pr@starmacro 284 \long\def\pr@protect@domacro#1#2{\pr@protect{%
285   \long\def\next##1{#2}%
286   \pr@callafter\next#1\pr@endparse}}
287 \newcommand\pr@starmacro[1][\]{\toks@{\pr@protect@domacro{#1}}%
288   \long\edef\next[##1]##2{%
289     \noexpand\pr@advise##2{\the\toks@{##1}}}%
290   \@ifnextchar[\next{\next[]}}

```

`\PreviewOpen` As explained above. Detect possible `*` and call appropriate macro.

```

291 \def\PreviewOpen{\@ifstar\pr@starmacro\pr@open}

```

The version without `*` is now rather straightforward.

`\pr@open`

```
292 \newcommand\pr@open[1] [] {%
293   \toks@{\pr@domacro{#1}}%
294   \long\edef\next[##1]##2{%
295     \noexpand\pr@advise##2{\begingroup
296       \noexpand\pr@protect@ship
297       {\the\toks@{\begingroup\aftergroup\noexpand\pr@endbox##1}}}%
298     {\endgroup}}}%
299   \@ifnextchar[\next\pr@macroii}
```

`\PreviewClose` As explained above. Detect possible `*` and call appropriate macro.

```
300 \def\PreviewClose{\@ifstar\pr@starmacro\pr@close}
```

The version without `*` is now rather straightforward.

`\pr@close`

```
301 \newcommand\pr@close[1] [] {%
302   \toks@{\pr@domacro{#1}}%
303   \long\edef\next[##1]##2{%
304     \noexpand\pr@advise{##2}{\the\toks@{##1\endgroup}}}%
305   \@ifnextchar[\next\pr@macroii}
```

`\PreviewEnvironment` Actually, this ignores any syntax argument. But don't tell anybody. Except for the `*` variant, it respects (actually ignores) any argument! Of course, we'll need to deactivate `\end{environment}` as well.

```
306 \def\PreviewEnvironment{\@ifstar\pr@starenv\pr@env}
307 \newcommand\pr@starenv[1] [] {\toks@{\pr@starmacro[{#1}]}}%
308 \long\edef\next##1##2{%
309   \the\toks@[{##2}]##1}%
310 \begingroup\pr@starenvii}
311 \newcommand\pr@starenvii[2] [] {\endgroup
312   \expandafter\next\csname#2\endcsname{#1}%
313   \expandafter\pr@starmacro\csname end#2\endcsname}
314 \newcommand\pr@env[1] [] {%
315   \toks@{\pr@domacro{#1}}%
316   \long\edef\next[##1]##2{%
317     \noexpand\expandafter\noexpand\pr@advise@ship
318     \noexpand\csname##2\noexpand\endcsname{\the\toks@
319       {\begingroup\aftergroup\noexpand\pr@endbox##1}}{\endgroup}}%
320   \@ifnextchar[\next\pr@macroii %]
321 }
```

`\PreviewSnarfEnvironment` This is a nuisance since we have to advise *both* the environment and its end.

```
322 \newcommand{\PreviewSnarfEnvironment}[2] [] {%
323   \expandafter\pr@advise
324   \csname #2\endcsname{\pr@snarfafter{#1}}%
325   \expandafter\pr@advise
326   \csname end#2\endcsname{\pr@endsnarf}}
327 </!active>
```

`\pr@snarf@after` Ok, this looks complicated, but we have to start a group in order to be able to  
`\pr@startsnarf` hook `\pr@endbox` into the game only when `\ifpr@outer` has triggered the start.  
`\pr@endsnarf` And we need to get our start messages out before parsing the arguments.

```

328 <*active>
329 \let\pr@endsnarf\relax
330 \long\def\pr@snarf@after#1{\ifpr@outer
331     \pr@ship@start
332     \let\pr@ship@start\relax
333     \let\pr@endsnarf\endgroup
334 \else
335     \let\pr@endsnarf\relax
336 \fi
337 \pr@protect{\pr@call@after\pr@startsnarf#1]\pr@endparse}}
338 \def\pr@startsnarf#1{#1\begin{group}
339     \pr@startbox{\begin{group}\aftergroup\pr@endbox}\end{group}}%
340 \ignorespaces}
341 </active>

```

`\pr@ship@start` The hooks `\pr@ship@start` and `\pr@ship@end` can be added to by option  
`\pr@ship@end` files by the help of the `\g@addto@macro` command from L<sup>A</sup>T<sub>E</sub>X, and by the  
`\pr@addto@front` command from `preview.sty` itself. They are called just be-  
fore starting to process some preview, and just after it. Here is the policy for  
adding to them: `\pr@ship@start` is called inside of the vbox `\pr@box` before  
typeset material gets produced. It is, however, preceded by a break command  
that is intended for usage in `\vsplit`, so that any following glue might disappear.  
In case you want to add any material on the list, you have to precede it with  
`\unpenalty` and have to follow it with `\break`. You have make sure that under  
no circumstances any other legal breakpoints appear before that, and your mate-  
rial should contribute no nonzero dimensions to the page. For the policies of the  
`\pr@ship@end` hook, see the description on page 12.

```

342 <!*active>
343 \let\pr@ship@start\@empty
344 \let\pr@ship@end\@empty

```

`preview` First we write the definitions of these environments when `preview` is inactive. We  
`nopreview` will redefine them if `preview` gets activated.

```

345 \newenvironment{preview}{\ignorespaces}\ifhmode\unskip\fi}
346 \newenvironment{nopreview}{\ignorespaces}\ifhmode\unskip\fi}

```

We now process the options and finish in case we are not active.

```

347 \ProcessOptions\relax
348 \ifPreview\else\expandafter\endinput\fi
349 </!active>

```

Now for the redefinition of the `preview` and `endpreview` environments:

```

350 <*active>
351 \renewenvironment{preview}{\begin{group}
352     \pr@startbox{\begin{group}\aftergroup\pr@endbox}}%

```

```

353         {\endgroup}%
354     \ignorespaces}%
355     {\ifhmode\unskip\fi\endgroup}
356 \renewenvironment{nopreview}{\pr@outerfalse\ignorespaces}%
357     {\ifhmode\unskip\fi}

```

We use the normal output routine, but hijack it a bit for our purposes to preserve `\AtBeginDvi` hooks and not get previews while in output: that could become rather ugly.

The main work of disabling normal output relies on a `\shipout` redefinition.

`\pr@output`

```

358 \newtoks\pr@output
359 \pr@output\output
360 \output{%
361     \pr@outerfalse
362     \let\@begindvi\@empty
363     \the\pr@output}
364 \let\output\pr@output

```

`\pr@typeinfos` Then we have some document info that style files might want to output.

```

365 \def\pr@typeinfos{\typeout{Preview: Fontsize \f@size pt}}%
366 \ifnum\mag=\@m\else\typeout{Preview: Magnification \number\mag}\fi
367 \ifx\pdfoutput\@undefined
368     \ifx\XeTeXversion\@undefined \else
369         % FIXME: The message should not be emitted if XeTeX does not produce
370         % PDF. There does not seem to be a primitive for that, though.
371         \typeout{Preview: PDFoutput 1}%
372     \fi
373 \else
374     \ifx\pdfoutput\relax \else
375         \ifnum\pdfoutput>\z@
376             \typeout{Preview: PDFoutput 1}%
377         \fi
378     \fi
379 \fi
380 }
381 \AtBeginDocument{\pr@typeinfos}

```

And at the end we load the default configuration file, so that it may override settings from this package:

```

382 \pr@loadcfg{prdefault}
383 \</active>
384 \</style>

```

## 5 The option files

### 5.1 The auctex option

The AUCTEX option will cause error messages to spew. We want them on the terminal, but we don't want L<sup>A</sup>T<sub>E</sub>X to stop its automated run. We delay `\nonstopmode` in case the user has any pseudo-interactive folderol like reading in of file names in his preamble. Because we are so good-hearted, we will not break this as long as the document has not started, but after that we need the error message mechanism operative.

The `\nofiles` command here tries to avoid clobbering input files used for references and similar. It will come too late if you call the package with `\AtBeginDocument`, so you'll need to issue `\nofiles` yourself in that case. Previously, this was done unconditionally in the main style file, but since we don't know what the package may be used for, this was inappropriate.

So here is the contents of the `prauctex.def` file:

```
385 <auctex>\ifPreview\else\expandafter\endinput\fi
386 <auctex>\nofiles
387 <auctex>\preview@delay{\nonstopmode}
```

Ok, here comes creative error message formatting. It turns out a sizable portion of the runtime is spent in I/O. Making the error messages short is an advantage. It is not possible to convince T<sub>E</sub>X to make shorter error messages than this: T<sub>E</sub>X always wants to include context. This is about the shortest æsthetic one we can muster.

```
388 <auctex>\begingroup
389 <auctex>\lccode'\~='\'-
390 <auctex>\lccode'\{='\'<
391 <auctex>\lccode'\}='\'>
392 <auctex>\lowercase{\endgroup
393 <auctex> \def\pr@msgi{{~}}
394 <auctex>\def\pr@msgii{Preview:
395 <auctex> Snippet \number\pr@snippet\space}
396 <auctex>\begingroup
397 <auctex>\catcode'\-=13
398 <auctex>\catcode'\<=13
399 <auctex>\@firstofone{\endgroup
400 <auctex>\def\pr@msg#1{{%
401 <auctex> \let<\pr@msgi
402 <auctex> \def-{\pr@msgii#1}%
403 <auctex> \errhelp{Not a real error.}%
404 <auctex> \errmessage<}}
405 <auctex>\g@addto@macro\pr@ship@start{\pr@msg{started}}
406 <auctex>\g@addto@macro\pr@ship@end{\pr@msg{ended.%
407 <auctex> (\number\ht\pr@box+\number\dp\pr@box x\number\wd\pr@box)}}}
```

This looks pretty baffling, but it produces something short and semi-graphical, namely `<-><->`. That is a macro `<` that expands into `<->`, where `<` and `>` are the braces around an `\errmessage` argument and `-` is a macro expanding to the full

text of the error message. Cough cough. You did not really want to know, did you?

Since over/underfull boxes are about the messiest things to parse, we disable them by setting the appropriate badness limits and making the variables point to junk. We also disable other stuff. While we set `\showboxbreadth` and `\showboxdepth` to indicate as little diagnostic output as possible, we keep them operative, so that the user retains the option of debugging using this stuff. The other variables concerning the generation of warnings and daignostics, however, are more often set by commonly employed packages and macros such as `\sloppy`. So we kill them off for good.

```
408 <auctex>\hbadness=\maxdimen
409 <auctex>\newcount\hbadness
410 <auctex>\vbadness=\maxdimen
411 <auctex>\let\vbadness=\hbadness
412 <auctex>\hfuzz=\maxdimen
413 <auctex>\newdimen\hfuzz
414 <auctex>\vfuzz=\maxdimen
415 <auctex>\let\vfuzz=\hfuzz
416 <auctex>\showboxdepth=-1
417 <auctex>\showboxbreadth=-1
```

Ok, now we load a possible configuration file.

```
418 <auctex>\pr@loadcfg{prauctex}
```

And here we cater for several frequently used commands in `prauctex.cfg`:

```
419 <auccfg>\PreviewMacro*[] [#1{}]\footnote
420 <auccfg>\PreviewMacro*[?[@{[]}]{}] [#1]\item
421 <auccfg>\PreviewMacro*\emph
422 <auccfg>\PreviewMacro*\textrm
423 <auccfg>\PreviewMacro*\textit
424 <auccfg>\PreviewMacro*\textsc
425 <auccfg>\PreviewMacro*\textsf
426 <auccfg>\PreviewMacro*\textsl
427 <auccfg>\PreviewMacro*\texttt
428 <auccfg>\PreviewMacro*\textcolor
429 <auccfg>\PreviewMacro*\mbox
430 <auccfg>\PreviewMacro*[] [#1{}]\author
431 <auccfg>\PreviewMacro*[] [#1{}]\title
432 <auccfg>\PreviewMacro*\and
433 <auccfg>\PreviewMacro*\thanks
434 <auccfg>\PreviewMacro*[] [#1{}]\caption
435 <auccfg>\preview@delay{\@ifundefined{pr@\string\@startsection}{%
436 <auccfg> \PreviewMacro*[!!!!*] [#1{}]\@startsection}{}}
437 <auccfg>\preview@delay{\@ifundefined{pr@\string\chapter}{%
438 <auccfg> \PreviewMacro*[*] [#1{}]\chapter}{}}
439 <auccfg>\PreviewMacro*\index
```

## 5.2 The lyx option

The following is the option providing LyX with info for its preview implementation.

```
440 <lyx>\ifPreview\else\expandafter\endinput\fi
441 <lyx>\pr@loadcfg{prlyx}
442 <lyx>\g@addto@macro\pr@ship@end{\typeout{Preview:
443 <lyx> Snippet \number\pr@snippet\space
444 <lyx> \number\ht\pr@box\space \number\dp\pr@box \space\number\wd\pr@box}}
```

## 5.3 The counters option

This outputs a checkpoint. We do this by saving all counter registers in backup macros starting with `\pr@c@` in their name. A checkpoint first writes out all changed counters (previously unchecked counters are not written out unless different from zero), then saves all involved counter values. L<sup>A</sup>T<sub>E</sub>X tracks its counters in the global variable `\cl@ckpt`.

```
445 <counters>\ifPreview\else\expandafter\endinput\fi
446 <counters>\def\pr@eltprint#1{\expandafter\@gobble\ifnum\value{#1}=0%
447 <counters> \csname pr@c@#1\endcsname\else\relax
448 <counters> \space{#1}{\arabic{#1}}\fi}
449 <counters>\def\pr@eltdef#1{\expandafter\xdef
450 <counters> \csname pr@c@#1\endcsname{\arabic{#1}}}
451 <counters>\def\pr@ckpt#1{{\let\@elt\pr@eltprint\edef\next{\cl@ckpt}%
452 <counters> \ifx\next\@empty\else\typeout{Preview: Counters\next#1}%
453 <counters> \let\@elt\pr@eltdef\cl@ckpt\fi}}
454 <counters>\pr@addto@front\pr@ship@start{\pr@ckpt:}
455 <counters>\pr@addto@front\pr@ship@end{\pr@ckpt.}
```

## 5.4 Debugging options

Those are for debugging the operation of `preview`, and thus are mostly of interest for people that want to use `preview` for their own purposes. Since debugging output is potentially confusing to the error message parsing from AUCT<sub>E</sub>X, you should not turn on `\tracingonline` or switch from `\nonstopmode` unless you are certain your package will never be used with `preview-latex`.

**The showbox option** will generate diagnostic output for every produced box. It does not delay the resetting of the `\showboxbreadth` and `\showboxdepth` parameters so that you can still change them after the loading of the package. It does, however, move them to the end of the package loading, so that they will not be affected by the `auctex` option.

```
456 <showbox>\ifPreview\else\expandafter\endinput\fi
457 <showbox>\AtEndOfPackage{%
458 <showbox> \showboxbreadth\maxdimen
459 <showbox> \showboxdepth\maxdimen}
460 <showbox>\g@addto@macro\pr@ship@end{\showbox\pr@box}
```



The `tracingall` option is for the really heavy diagnostic stuff. For the reasons mentioned above, we do not want to change the setting of the interaction mode, nor of the `tracingonline` flag. If the user wants them different, he should set them outside of the preview boxes.

```
461 <tracingall>\ifPreview\else\expandafter\endinput\fi
462 <tracingall>\pr@addto@front\pr@ship@start{\let\tracingonline\count@
463 <tracingall> \let\errorstopmode\@empty\tracingall}
```

## 5.5 Supporting conversions

It is not uncommon to want to use the results of `preview` as images. One possibility is to generate a flurry of EPS files with

```
dvips -E -i -Ppdf -o <outputfile>.000 <inputfile>
```

However, in case those are to be processed further into graphic image files by Ghostscript, this process is inefficient. One cannot use Ghostscript in a single run for generating the files, however, since one needs to set the page size (or full size pages will be produced). The `tightpage` option will set the page dimensions at the start of each PostScript page so that the output will be sized appropriately. That way, a single pass of Dvips followed by a single pass of Ghostscript will be sufficient for generating all images.

You will have to specify the output driver to be used, either `dvips` or `pdftex`.

`\PreviewBorder` We start this off with the user tunable parameters which get defined even in the  
`\PreviewBbAdjust` case of an inactive package, so that redefinitions and assignments to them will always work:

```
464 <tightpage>\ifx\PreviewBorder\@undefined
465 <tightpage> \newdimen\PreviewBorder
466 <tightpage> \PreviewBorder=0.50001bp
467 <tightpage>\fi
468 <tightpage>\ifx\PreviewBbAdjust\@undefined
469 <tightpage> \def\PreviewBbAdjust{-\PreviewBorder -\PreviewBorder
470 <tightpage> \PreviewBorder \PreviewBorder}
471 <tightpage>\fi
```

Here is stuff used for parsing this:

```
472 <tightpage>\ifPreview\else\expandafter\endinput\fi
473 <tightpage>\def\pr@nextbb{\edef\next{\next\space\number\dimen@}%
474 <tightpage> \expandafter\xdef\csname pr@bb@%
475 <tightpage> \romannumeral\count@\endcsname{\the\dimen@}%
476 <tightpage> \advance\count@\@ne\ifnum\count@<5
477 <tightpage> \afterassignment\pr@nextbb\dimen@=\fi}
```

And here is the stuff that we fudge into our hook. Of course, we have to do it in a box, and we start this box off with our special. There is one small consideration here: it might come before any `\AtBeginDvi` stuff containing header specials. It turns out Dvips rearranges this amicably: header code specials get transferred to the appropriate header section, anyhow, so this ensures that we come right after

the bop section. We insert the 7 numbers here: the 4 bounding box adjustments, and the 3 TeX box dimensions. In case the box adjustments have changed since the last time, we write them out to the console.

```

478 <tightpage>\ifnum\pr@graphicstype=\z@
479 <tightpage> \ifcase
480 <tightpage> \ifx\XeTeXversion\@undefined
481 <tightpage> \ifx\pdfoutput\@undefined \@ne\fi
482 <tightpage> \ifx\pdfoutput\relax \@ne\fi
483 <tightpage> \ifnum\pdfoutput>\z@ \tw@\fi \@ne
484 <tightpage> \else \thr@@\fi
485 <tightpage> \or \ExecuteOptions{dvips}\relax
486 <tightpage> \or \ExecuteOptions{pdftex}\relax
487 <tightpage> \or \ExecuteOptions{xetex}\relax\fi\fi
488 <tightpage>\global\let\pr@bbadjust\@empty
489 <tightpage>\pr@addto@front\pr@ship@end{\begingroup
490 <tightpage> \let\next\@gobble
491 <tightpage> \count@\@ne\afterassignment\pr@nextbb
492 <tightpage> \dimen@\PreviewBbAdjust
493 <tightpage> \ifx\pr@bbadjust\next
494 <tightpage> \else \global\let\pr@bbadjust\next
495 <tightpage> \typeout{Preview: Tightpage \pr@bbadjust}%
496 <tightpage> \fi\endgroup}
497 <tightpage>\ifcase\pr@graphicstype
498 <tightpage>\or
499 <tightpage> \g@addto@macro\pr@ship@end{\setbox\pr@box\hbox{%
500 <tightpage> \special{ps::\pr@bbadjust\space
501 <tightpage> \number\ifdim\ht\pr@box>\z@ \ht\pr@box
502 <tightpage> \else \z@
503 <tightpage> \fi \space
504 <tightpage> \number\ifdim\dp\pr@box>\z@ \dp\pr@box
505 <tightpage> \else \z@
506 <tightpage> \fi \space
507 <tightpage> \number\ifdim\wd\pr@box>\z@ \wd\pr@box
508 <tightpage> \else \z@
509 <tightpage> \fi}\box\pr@box}}
510 <tightpage>\or
511 <tightpage> \g@addto@macro\pr@ship@end{{\dimen@\ht\pr@box
512 <tightpage> \ifdim\dimen@<\z@ \dimen@\z@\fi
513 <tightpage> \advance\dimen@\pr@bb@iv
514 <tightpage> \dimen@ii=\dimen@
515 <tightpage> \global\pdfvorigin\dimen@
516 <tightpage> \dimen@\dp\pr@box
517 <tightpage> \ifdim\dimen@<\z@ \dimen@\z@\fi
518 <tightpage> \advance\dimen@-\pr@bb@ii
519 <tightpage> \advance\dimen@\dimen@ii
520 <tightpage> \global\pdfpageheight\dimen@
521 <tightpage> \dimen@\wd\pr@box
522 <tightpage> \ifdim\dimen@<\z@ \dimen@=\z@\fi
523 <tightpage> \advance\dimen@-\pr@bb@i

```

```

524 <tightpage> \advance\dimen@ \pr@bb@iii
525 <tightpage> \global\pdfpagewidth\dimen@
526 <tightpage> \global\pdfhorigin-\pr@bb@i}}
527 <tightpage> \or
528 <tightpage> \g@addto@macro\pr@ship@end{\dimen@\ht\pr@box
529 <tightpage> \ifdim\dimen@<\z@ \dimen@\z@\fi
530 <tightpage> \advance\dimen@ \pr@bb@iv
531 <tightpage> \dimen@ii=\dimen@
532 <tightpage> \voffset=-1in
533 <tightpage> \advance\voffset\dimen@
534 <tightpage> \advance\voffset-\ht\pr@box
535 <tightpage> \dimen@\dp\pr@box
536 <tightpage> \ifdim\dimen@<\z@ \dimen@\z@\fi
537 <tightpage> \advance\dimen@-\pr@bb@ii
538 <tightpage> \advance\dimen@\dimen@ii
539 <tightpage> \global\pdfpageheight\dimen@
540 <tightpage> \global\paperheight\dimen@
541 <tightpage> \dimen@\wd\pr@box
542 <tightpage> \ifdim\dimen@<\z@ \dimen@=\z@\fi
543 <tightpage> \advance\dimen@-\pr@bb@i
544 <tightpage> \advance\dimen@ \pr@bb@iii
545 <tightpage> \global\pdfpagewidth\dimen@
546 <tightpage> \hoffset=-1in
547 <tightpage> \advance\hoffset-\pr@bb@i
548 <tightpage> \let\pr@offset@override@empty}
549 <tightpage> \fi

```

Ok, here comes the beef. First we fish the 7 numbers from the file with `token` and convert them from T<sub>E</sub>X `sp` to PostScript points.

```

550 <tightpage> \ifnum\pr@graphicstype=\@ne
551 <tightpage> \preview@delay{\AtBeginDvi{%

```

Backwards-compatibility. Once we are certain that dvipng-1.6 or later is widely used, the three following specials can be exchanged for the simple `\special{!/preview@tightpage true def}`

```

552 <tightpage> \special{!/preview@tightpage true def (%)
553 <tightpage> compatibility PostScript comment for dvipng<=1.5 }
554 <tightpage> \special{!userdict begin/bop-hook{%
555 <tightpage> 7{currentfile token not{stop}if
556 <tightpage> 65781.76 div DVImag mul}repeat
557 <tightpage> 72 add 72 2 copy gt{exch}if 4 2 roll
558 <tightpage> neg 2 copy lt{exch}if dup 0 gt{pop 0 exch}%
559 <tightpage> {exch dup 0 lt{pop 0}if}ifelse 720 add exch 720 add
560 <tightpage> 3 1 roll
561 <tightpage> 4{5 -1 roll add 4 1 roll}repeat
562 <tightpage> <</PageSize[5 -1 roll 6 index sub 5 -1 roll 5 index sub]%
563 <tightpage> /PageOffset[7 -2 roll [1 1 dtransform exch]%
564 <tightpage> {0 ge{neg}if exch}forall]>>setpagedevice%
565 <tightpage> //bop-hook exec}bind def end}
566 <tightpage> \special{!userdict (some extra code to avoid

```

```

567 <tightpage>      dvipng>=1.6 unknown special:
568 <tightpage>      7{currentfile token not{stop}if 65781.76 div }))) pop}
  The “userdict” at the start of the last special is also there to avoid an unknown
  special in dvipng=1.6. This is the end of the backwards-compatibility code.
569 <tightpage>      \special{!userdict begin/bop-hook{%
570 <tightpage>      preview-bop-level 0 le{%
571 <tightpage>      7{currentfile token not{stop}if
572 <tightpage>      65781.76 div DVImag mul}repeat

```

Next we produce the horizontal part of the bounding box as

$$(1in, 1in) + (\min(\wd\pr@box, 0), \max(\wd\pr@box, 0))$$

and roll it to the bottom of the stack:

```

573 <tightpage>      72 add 72 2 copy gt{exch}if 4 2 roll

```

Next is the vertical part of the bounding box. Depth counts in negatively, and we again take min and max of possible extents in the vertical direction, limited by 0. 720 corresponds to 10in and is the famous 1 in distance away from the edge of letterpaper.

```

574 <tightpage>      neg 2 copy lt{exch}if dup 0 gt{pop 0 exch}%
575 <tightpage>      {exch dup 0 lt{pop 0}if}ifelse 720 add exch 720 add
576 <tightpage>      3 1 roll

```

Ok, we now have the bounding box on the stack in the proper order llx, lly, urx, ury. We add the adjustments:

```

577 <tightpage>      4{5 -1 roll add 4 1 roll}repeat

```

The page size is calculated as the appropriate differences, the page offset consists of the coordinates of the lower left corner, with those coordinates negated that would be reckoned positive in the device coordinate system.

```

578 <tightpage>      <</PageSize[5 -1 roll 6 index sub 5 -1 roll 5 index sub]%
579 <tightpage>      /PageOffset[7 -2 roll [1 1 dtransform exch]%
580 <tightpage>      {0 ge{neg}if exch}forall]>>setpagedevice}if%

```

So we now bind the old definition of bop-hook into our new definition and finish it.

```

581 <tightpage>      //bop-hook exec}bind def end}}}
582 <tightpage>\fi

```

## 5.6 The showlabels option

During the editing process, some people like to see the label names in their equations, figures and the like. Now if you are using Emacs for editing, and in particular `preview-latex`, I’d strongly recommend that you check out the `RefTeX` package which pretty much obliterates the need for this kind of functionality. If you still want it, standard  $\text{\LaTeX}$  provides it with the `showkeys` package, and there is also the less encompassing `showlabels` package. Unfortunately, since those go to some pain not to change the page layout and spacing, they also don’t change `preview`’s idea of the  $\text{\TeX}$  dimensions of the involved boxes.

So those packages are mostly useless. So we present here an alternative hack that will get the labels through.

`\pr@labelbox` This works by collecting them into a separate box which we then tack to the right of the previews.

```
583 <showlabels>\ifPreview\else\expandafter\endinput\fi
584 <showlabels>\newbox\pr@labelbox
```

`\pr@label` We follow up with our own definition of the `\label` macro which will be active only in previews. The original definition is stored in `\pr@@label`. `\pr@lastlabel` contains the last typeset label in order to avoid duplication in certain environments, and we keep the stuff in `\pr@labelbox`.

```
585 <showlabels>\def\pr@label#1{\pr@@label{#1}%
```

Ok, now we generate the box, by placing the label below any existing stuff.

```
586 <showlabels> \ifpr@setbox\z@{#1}%
587 <showlabels> \global\setbox\pr@labelbox\vbox{\unvbox\pr@labelbox
588 <showlabels> \box\z@}\egroup\fi}
```

`\ifpr@setbox` `\ifpr@setbox` receives two arguments, `#1` is the box into which to set a label, `#2` is the label text itself. If a label needs to be set (if it is not a duplicate in the current box, and is nonempty, and we are in the course of typesetting and so on), we are left in a true conditional and an open group with the preset box. If nothing should be set, no group is opened, and we get into skipping to the closing of the conditional. Since `\ifpr@setbox` is a macro, you should not place the call to it into conditional text, since it will not pair up with `\fi` until being expanded.

We have some trickery involved here. `\romannumeral\z@` expands to empty, and will also remove everything between the two of them that also expands to empty, like a chain of `\fi`.

```
589 <showlabels>\def\ifpr@setbox#1#2{%
590 <showlabels> \romannumeral%
591 <showlabels> \ifx\protect\@typeset@protect\ifpr@outer\else
Ignore empty labels...
592 <showlabels> \z@\bgroup
593 <showlabels> \protected@edef\next{#2}\@onelevel@sanitize\next
594 <showlabels> \ifx\next\@empty\egroup\romannumeral\else
and labels equal to the last one.
595 <showlabels> \ifx\next\pr@lastlabel\egroup\romannumeral\else
596 <showlabels> \global\let\pr@lastlabel\next
597 <showlabels> \setbox#1\pr@boxlabel\pr@lastlabel
598 <showlabels> \expandafter\expandafter\romannumeral\fi\fi\fi\fi
599 <showlabels> \z@\iffalse\iftrue\fi}
```

`\pr@boxlabel` Now the actual typesetting of a label box is done. We use a small typewriter font inside of a framed box (the default frame/box separating distance is a bit large).

```
600 <showlabels>\def\pr@boxlabel#1{\hbox{\normalfont
601 <showlabels> \footnotesize\ttfamily\fbboxsep0.4ex\relax\fbbox{#1}}}
```

`\pr@maketag` And here is a version for `amsmath` equations. They look better when the label is right beside the tag, so we place it there, but augment `\box\pr@labelbox` with an appropriate placeholder.

```
602 <showlabels> \def\pr@maketag#1{\pr@maketag{#1}%
603 <showlabels> \ifpr@setbox\z@{\df@label}%
604 <showlabels> \global\setbox\pr@labelbox\vbox{%
605 <showlabels> \hrule\@width\wd\z@\@height\z@
606 <showlabels> \unvbox\pr@labelbox}%
```

Set the width of the box to empty so that the label placement gets not disturbed, then append it.

```
607 <showlabels> \wd\z@\z@\box\z@ \egroup\fi}
```

`\pr@lastlabel` Ok, here is how we activate this: we clear out box and label info

```
608 <showlabels> \g@addto@macro\pr@ship@start{%
609 <showlabels> \global\setbox\pr@labelbox\box\voidb@x
610 <showlabels> \xdef\pr@lastlabel{}}%
```

The definitions above are global because we might be in any amount of nesting. We then reassign the appropriate labelling macros:

```
611 <showlabels> \global\let\pr@@label\label \let\label\pr@label
612 <showlabels> \global\let\pr@@maketag\maketag@@@
613 <showlabels> \let\maketag@@@\pr@maketag
614 <showlabels> }
```

Now all we have to do is to add the stuff to the box in question. The stuff at the front works around a bug in `ntheorem.sty`.

```
615 <showlabels> \pr@addto@front\pr@ship@end{%
616 <showlabels> \ifx \label\pr@label \global\let\label\pr@@label \fi
617 <showlabels> \ifx \maketag@@@\pr@maketag
618 <showlabels> \global\let\maketag@@@\pr@maketag \fi
619 <showlabels> \ifvoid\pr@labelbox
620 <showlabels> \else \setbox\pr@box\hbox{%
621 <showlabels> \box\pr@box\,\box\pr@labelbox}%
622 <showlabels> \fi}
```

## 5.7 The footnotes option

This is rather simplistic right now. It overrides the default footnote action (which is to disable footnotes altogether for better visibility).

```
623 <footnotes> \PreviewMacro[!]\footnote %]
```

## 6 Various driver files

The installer, in case it is missing. If it is to be used via `make`, we don't specify an installation path, since

```
make install
```

is supposed to cater for the installation itself.

```
624 <installer> \input docstrip
625 <installer & make> \askforoverwritefalse
626 <installer> \generate{
627 <installer>   \file{preview.drv}{\from{preview.dtx}{driver}}
628 <installer&!make>   \usedir{tex/latex/preview}
629 <installer>   \file{preview.sty}{\from{preview.dtx}{style}
630 <installer>       \from{preview.dtx}{style,active}}
631 <installer>   \file{prauctex.def}{\from{preview.dtx}{auctex}}
632 <installer>   \file{prauctex.cfg}{\from{preview.dtx}{auccfg}}
633 <installer>   \file{prshowbox.def}{\from{preview.dtx}{showbox}}
634 <installer>   \file{prshowlabels.def}{\from{preview.dtx}{showlabels}}
635 <installer>   \file{prtracingall.def}{\from{preview.dtx}{tracingall}}
636 <installer>   \file{prtightpage.def}{\from{preview.dtx}{tightpage}}
637 <installer>   \file{prlyx.def}{\from{preview.dtx}{lyx}}
638 <installer>   \file{prcounters.def}{\from{preview.dtx}{counters}}
639 <installer>   \file{prfootnotes.def}{\from{preview.dtx}{footnotes}}
640 <installer> }
641 <installer> \endbatchfile
```

And here comes the documentation driver.

```
642 <driver> \documentclass{ltxdoc}
643 <driver> \usepackage{preview}
644 <driver> \let\ifPreview\relax
645 <driver> \newcommand\previewlatex{\texttt{preview-latex}}
646 <driver> \begin{document}
647 <driver> \DocInput{preview.dtx}
648 <driver> \end{document}
```